

Efficient, Reliable, Cost Effective



ClimaControl System MFT (Misting Fan Technology) Series

Incorporating



Ambient temperature and environmental space management system bridging the gap between air-conditioning and conventional fan systems

Product Range



Standalone System

èSoffio 360° Built-in Pump Motor Water Tank Wheels with Security Brake

Simple In Concept And Easy To Install

Cooling at 360° by Idrobase Group uses a 360° fan, placed at a height of 2.5 meters. Millions of microdroplets of water, atomized at high pressure, are blown through a ring of nozzles set around the fan 360° forming a sort of cloud. In absence of wind, such cloud has a diameter of 6 meters and covers an area of 30 square meters around the fan. These millions of tiny water droplets hover in the air and then, while evaporating, absorb heat from the environment, reducing the temperature in the surrounding area up to 10°C, without wetting people and objects.



Negative lons for Health



Sensibly Reduce Temperature

Humidity Control

Odour Control



Keep Mosquitoes Away



No Wet





Fog 40

The most effective solution for cooling, creating special effects, humidification, dust suppression and odour control in small and medium sized areas, designed to feed 360° cooling systems.

Energy Saving



Fog 40 Specifications:

- · Frame made of galvanized plate with stainless steel cover.
- Motor-brass blade pump, 1450Rpm, 375W 230V-50Hz, flow rate:70l/h, pressure: 40bar.
- L.P. solenoid valve 230V-50Hz, inlet water.
- H.P. solenoid valve 230V-50Hz, to unload the high pressure line.
- L.P. pressure switch for shortage of water.
- By-pass valve.
- Electric board complete with ON/OFF thermal switch, remote control switch and timer to relay H.P. solenoid valve. Ready to be connected to external device (tank level sensor, fans, lights, UV lamp).
- · Remote control: maximum 30 meter with 4 channels, set up with power button on and off, setting time of 3 PAUSE / WORK, ON and OFF lights.
- Weight: 15kg, dimensions: 250cm x 390cm x 210cm.

Sensibly Reduce Temperature

Humidity Control

Odour Control







No Wet

Negative lons for Health

Dust Suppression





Fan 360° Series

Fan 360° Series is an extraordinary new product in the fog sector, its radial diffusion at 360° allows six-times-bigger coverage than traditional online systems, increasing the effectiveness of sprinkler systems. Perfect for both cooling and humidification indoors or in semi-open areas.



High Performance



Fan 360° Pedestal

Base support and 2-piece stick (Dimensions: 270 cm height)



Fan 360° Specifications:

- Frame: painted steel.
- Electric motor: 1375Rpm, 230V/50Hz, 96W, 0.47A.
- ON/OFF switch.
- Noise: 59dB.
- Air capacity: 4000m³/h.
- Flow range: 3m 4m.
- 6-hole ring threaded 12/24UNC/A.
- 6 stainless steel nickel coated nozzles with hole 0.15mm.

Sensibly Reduce Temperature

Humidity Control

Odour Control



Keep Mosquitoes Away









Fan 360°

Rod support to fix the fan on the ceiling

Ceiling

PATENTED TECHNOLOGY

Modular and Flexible

High Reliability



Dust Suppression



Negative Ions for Health





Ombrellone 360°



Ombrellone 360° Specifications:

- Fan 360° with ring and 6 fog nozzles, hole 0.15mm.
- Fog 40, 40 bar.
- 50-litre water tank.
- Frame and cover for Fog 40 and tank.
- High pressure polyamide pipe ø6.35mm (8m).
- Umbrella 3.5m x 3.5m with manual opening, base 25cm x 25cm.
- 4 white armchairs made of stainless steel AISI 304 and weaving in synthetic resin.
- White table with base in stainless steel AISI 304 and table weaving in synthetic resin.

Sensibly Reduce Temperature

Humidity Control

Odour Control



Keep Mosquitoes Away





Negative lons for Health



Tavelino 360°



Sensibly Reduce Temperature

Humidity Control

Odour Control



Keep Mosquitoes Away







èSoffio 360°

190 cm 11,8"

èSoffio 360° is a portable air-conditioner, powerful and highly efficient, and can be moved anywhere you want to create havens of comfort even on the hottest days. èSoffio 360° sprays a micronized water mist with a powerful ventilation system, ensuring instant and lasting cooling of ambient temperature.





High Performance

High Reliability



Modular and Flexible



Dust Suppression



Negative lons for Health



èSoffio 360° Specifications: • Crankshaft pump 0.5 l/min, flow rate: 3

- Crankshaft pump 0.5 l/min, flow rate: 30 l/h, pressure: 70bar, with thermal protection.
- Electric motor 230V-50Hz, 390W, 1.53A.
- Stops automatically on shortage of water.
- Integrated digital timer sets the duty cycle, manual and automatic working, 24 hours scheduling. Alarm on shortage of water.
- 40-litre water tank (5 hours autonomy with timer at 50%).
- Direct connection to water supply.
- Wheels with security brake.
- Weight: 50kg, dimensions: 60cm x 52cm x 192cm.

Sensibly Reduce Temperature

Humidity Control

Odour Control



Keep Mosquitoes Away



No Wet





"Made in Italy"

Idrobase Group has twenty years experience in designing and producing fogging systems. The "Made in Italy" logo points out the use of high quality materials and the advanced know-how achieved by the company staff. This choice gives us the possibility to always find innovative solutions, suitable for our customers' requirements and for the needs of an evolving market.



Climatec Corp Pte Ltd

4 Changi North Street 1 | Hermes-Epitek Centre | Singapore 498816 Tel: (65) 6349 8992 | Fax: (65) 6349 8993 | sales@climatecsys.com | www.climatecsys.com